BILL'S HOME TECH

Home & Small Business Tech Solutions

AN EXTENDED GUIDE · NO. 2442

Updated November 2026

Will Solar Panels Wreck My Roof? Mounting, Flashing, and Leaks

How panels attach, why good flashing keeps water out, and how to avoid a leaky install

Plain-English tech help from:
Bill's Home Tech
Portage County, Ohio

Tech Made Simple. Service Made Personal.

Bill Davis — Bill's Home Tech
(330) 200-8042 · bill@billshometech.com · Atwater, Ohio

Book a visit · billshometech.com/book

What's Inside

Everything in this guide, with page numbers. Skip to whichever chapter answers your question right now.

The 60-Second Version 4
The Short Version 4
How Panels Attach to a Roof 5
Flashing: The Key to Staying Dry 5
Why a Good Install Protects the Roof 6
What a Bad Install Looks Like 7
The Old-Roof Trap 7
Does It Void My Roof Warranty? 8
The Installer's Workmanship Warranty 9
Catching a Problem Early 9
Removing Panels Later, If Needed 10
Questions That Protect Your Roof 10
Putting the Worry in Proportion 11
A Walkthrough — Checking Your Own Roof After an Install 12
How Mounting Differs by Roof Type 12
Red Flags During and After the Install 13
Common Myths About Solar and Roof Damage 13
Words You'll Hear 14
When to Call Bill 15
Everyday Cheat Sheet 16

A Note From Bill 17

Your Visit — and My Promise 18

SUMMARY

The 60-Second Version

Panels attach by bolting a frame through the roof into the rafters, so there are holes — and that is exactly where proper flashing does its job. Flashing layers metal and sealant around each point to guide water past, the same century-old craft that keeps chimneys dry. Done well by a careful pro, a solar install should not leak, and the panels even shelter the shingles beneath, so they age more slowly.

Done poorly — sealant smeared over a hole instead of real flashing, or an array rushed onto an old roof — it genuinely can leak. So the roof-leak question is really an installer-quality question. Replace an aging roof before solar, get a strong workmanship warranty on the penetrations in writing, and watch your ceilings after heavy rain rather than climbing up yourself.

- The holes aren't the problem; unsealed holes are — flashing is the answer.
- A good install shelters the roof; a careless one can leak.
- Fix an old roof first, and insist on a strong workmanship warranty.

1 The Short Version

One of the most common and sensible worries about going solar is this: will all those holes and hardware wreck my roof and cause leaks? It is a fair question, because panels do attach through the roof surface. The honest answer is that a properly installed system, done by a careful professional, should not harm your roof — and often protects the area it covers. Done poorly, though, it genuinely can cause leaks, so how it is installed matters enormously.

This guide explains how panels attach, why good flashing keeps water out, what a bad job looks like, and the questions that protect you. You will finish knowing the difference between a worry and a real risk, and how to make sure yours is the former.

- Panels attach through the roof, but proper flashing keeps those points watertight.

- A careful, professional install should not cause leaks and may shelter the roof beneath.
- A sloppy install genuinely can leak — the installer's skill is the whole ballgame.
- Replacing an old roof first avoids the biggest avoidable headache.

> **TIP**
>
> The roof-leak question is really an installer-quality question. The same holes, sealed correctly by a careful pro, stay watertight for decades; sealed carelessly, they can leak. Choosing the right installer is how you protect your roof.

2 How Panels Attach to a Roof

To judge the leak risk fairly, it helps to know how panels actually go on. Installers do not glue panels to the shingles; they bolt a frame to the roof's structure and clamp the panels to that frame. That means a number of attachment points penetrate the roof surface to reach the strong framing beneath.

Each of those penetration points is where water could, in theory, get in — and each is exactly where proper sealing and flashing do their job. The holes are not the problem; an unsealed hole would be. The craft of a good install is making every one of those points as watertight as the roof around it.

1. The installer locates the rafters — the strong framing under the roof.
2. Mounting feet are bolted through the roof into those rafters.
3. Each foot is sealed and flashed to keep water out (more on this next).
4. Rails attach to the feet, and panels clamp onto the rails.

3 Flashing: The Key to Staying Dry

Flashing is the quiet hero of a leak-free solar install. It is a method of layering metal and sealant around each roof penetration so that water running down the roof is guided over and around the hole rather than into it — the same proven technique used around chimneys and vents for generations.

Done right, flashing tucks under the shingles above the mounting foot and over the shingles below, so gravity carries water harmlessly past. This is a well-understood, time-tested craft. When people say a solar install 'shouldn't leak if done properly,' flashing is the biggest part of what 'properly' means.

GOOD TO KNOW

Think of flashing like the collar around a chimney. Chimneys pass through roofs everywhere and stay dry because of good flashing. Solar mounting points use the same principle — proven roofing craft, not a risky new idea.

4 Why a Good Install Protects the Roof

Here is a side you may not expect: the roof under your panels is often better protected than the rest of your roof, not worse. The panels act like a shield, taking the direct hit of sun, rain, hail, and snow, so the shingles beneath age more slowly, out of the harshest weather.

So while the attachment points are a risk to manage, the covered area as a whole frequently benefits. Many homeowners find the shingles under their panels look nearly new when the panels eventually come off. A well-installed array is less a threat to your roof than a parasol over much of it.

> *Panels take the beating so your shingles do not. Under a well-installed array, the roof often ages more gently than the bare roof around it — sheltered from the very sun and storms that wear shingles out.*

5 What a Bad Install Looks Like

Honesty requires naming the real risk: a careless install genuinely can leak, and it is worth knowing what cutting corners looks like. Most solar roof leaks trace back to poor workmanship at the attachment points, not to the panels themselves.

- Mounting feet bolted into the roof without proper flashing, relying on sealant alone.
- Attachment points that miss the rafters and chew into weak decking.
- Sealant smeared over a hole as a shortcut instead of layered flashing.
- Penetrations made and then not sealed before weather moves in.
- An install rushed onto an old, failing roof that needed replacing first.

> **WATCH OUT**
>
> Sealant alone is not flashing. A foot held down with a glob of caulk and no proper flashing may hold for a season and leak later, once sun and weather break the sealant down. Proper flashing, not caulk, is what keeps a penetration dry for decades.

6 The Old-Roof Trap

The single most avoidable roof problem with solar is installing on a roof that was already near the end of its life. Panels are meant to stay up for twenty-five years or more. If the shingles underneath fail in five, you face the costly job of removing the array, redoing the roof, and reinstalling the panels.

This is why the firm rule is to replace an aging roof before solar goes on, not after. A reputable installer inspects your roof's age and condition and will tell you honestly if it should be replaced first. One who ignores a tired roof to make a faster sale is setting you up for exactly the headache you fear.

WATCH OUT

If your roof has only a few years left, deal with it before the panels. Pulling an array off and putting it back to replace shingles is an expensive, avoidable job — and it is the most common way a solar project turns into a roof headache.

Rather not do this yourself? I'll come to your home and set it up for you — a flat $99 first visit across Portage County, Ohio and nearby communities. Outside the area? I also help remotely by phone or screen-share. Book at billshometech.com/book or call (330) 200-8042.

7 Does It Void My Roof Warranty?

A fair concern is whether drilling into the roof voids any existing roof or shingle warranty. The answer depends on your specific warranty and who does the work, so it is worth checking before you commit rather than discovering it afterward.

- Some roof warranties can be affected by penetrations from another trade.
- A reputable solar installer often provides their own workmanship warranty on the roof penetrations.
- Coordinating with your roofer, or using one who does both, can keep coverage intact.
- Get any warranty impact in writing before the work begins.

GOOD TO KNOW

This is a question to ask up front, in plain terms: 'Will this affect my existing roof warranty, and what do you warrant on the penetrations you make?' A good installer will have a clear, confident answer and put it in writing.

8 The Installer's Workmanship Warranty

Your best protection against roof leaks is the installer's own workmanship warranty — their written promise to stand behind the installation, including the roof penetrations, for a set number of years. This matters more here than almost anywhere, because a leak often shows up a while after the work, not the day it is done.

A strong installer offers a meaningful workmanship warranty, often ten years or more, covering leaks caused by their work. A short or vague one tells you how much they trust their own flashing. This is a case where the length and clarity of the promise genuinely protect your home.

> **TIP**
> When comparing installers, weigh the workmanship warranty heavily. A company that warrants its roof penetrations for ten-plus years is confident in its flashing — and will still be the one you call if a drip ever appears.

9 Catching a Problem Early

If a leak ever does start, catching it early keeps a small issue from becoming a big one. You do not need to climb anything; you watch for signs from inside and below, as you would for any roof leak.

1. After heavy rain or snowmelt, glance at ceilings and the attic near the array for stains or dampness.
2. Watch for new water marks, bubbling paint, or a musty smell indoors.
3. If you see a sign, note it and contact your installer promptly under the workmanship warranty.
4. Do not go up on the roof yourself to investigate — let a professional check it safely.

WATCH OUT

Never climb onto your roof to inspect panels or chase a leak. The small amount you might learn is not worth a fall. Watching from inside and calling your installer is both safer and more effective.

10 Removing Panels Later, If Needed

Sometimes panels must come off temporarily — to replace a roof, repair a leak, or fix storm damage — and it is reassuring to know this is a normal, routine job. The system is designed to be unclamped, lifted, and reinstalled, not to be permanent in a way that traps your roof.

It does cost money and should be done by professionals, which circles back to why replacing an old roof first is wise: you avoid paying for this removal and reinstall sooner than necessary. But knowing it can be done cleanly takes some of the fear out of committing to panels.

GOOD TO KNOW

Panels are not welded on forever. A qualified crew can remove and reinstall an array when a roof genuinely needs work. Planning the roof first simply spares you that cost earlier than you would like.

11 Questions That Protect Your Roof

These plain questions, asked before you sign, are your best defense against a roof problem.

- "How do you flash each mounting point to prevent leaks?"
- "Do you anchor into the rafters, and how do you locate them?"
- "What workmanship warranty do you offer on the roof penetrations, and for how long?"

- "Will this affect my existing roof warranty?"
- "Does my roof have enough life left, or should it be replaced first?"

WATCH OUT

Confident, specific answers — especially about flashing and the workmanship warranty — are the mark of an installer who will treat your roof with care. Vagueness on these is the clearest warning sign there is.

12 Putting the Worry in Proportion

It is worth ending with perspective. Roof leaks from solar are not common when the work is done well, and the technique that prevents them — flashing roof penetrations — is century-old roofing craft, not an experiment. The worry is reasonable, but it is almost entirely answered by choosing a careful, well-reviewed installer and dealing with an old roof first.

- A good install, properly flashed, should not leak — and shelters the roof beneath.
- The real risk is a careless install or an already-failing roof.
- A strong workmanship warranty is your written protection.
- Choosing the right installer is how you turn the risk into a non-issue.

> *The question is not really 'will panels damage my roof?' It is 'will this installer flash my roof properly and tell me honestly if it needs replacing first?' Answer that, and the roof worry answers itself.*

Rather not do this yourself? I'll come to your home and set it up for you — a flat $99 first visit across Portage County, Ohio and nearby communities. Outside the area? I also help remotely by phone or screen-share. Book at billshometech.com/book or call (330) 200-8042.

13 A Walkthrough — Checking Your Own Roof After an Install

You do not need to climb up to keep an eye on a solar install. A calm look from the ground and the attic, a couple of times a year and after big storms, catches almost anything worth catching early.

1. From the ground, look up at the mounts where they meet the roof — the flashing should sit flat and tidy, with no lifted shingles around it.
2. Scan for any shingle that looks loose, buckled, or out of line near the array.
3. After a heavy rain or snowmelt, step into the attic with a flashlight and look at the underside of the roof beneath the panels.
4. Check for any damp spots, dark stains, or streaks on the wood or insulation up there.
5. Note the date you checked; a quick yearly habit makes a slow problem obvious before it grows.

> **GOOD TO KNOW**
>
> A dry attic under the array after a hard rain is the single best sign the install is doing its job. Water shows up inside long before it shows up as a ceiling stain, so the attic is where you look first.

14 How Mounting Differs by Roof Type

How panels attach — and how the roof is kept watertight — depends a lot on what the roof is made of. Knowing the difference helps you ask the right question for your own home.

- Asphalt shingle: bolts go into the rafters and each hole is sealed and tucked under a metal flashing — the standard, well-proven method here.
- Standing-seam metal: clamps grip the raised seams, so often no holes are drilled at all — excellent for staying watertight.

- Tile or slate: tiles are carefully lifted and special hooks or flashings are fitted; this needs real experience with the material.
- Low-slope or flat: panels sit on a weighted or sealed frame, and the roofing membrane's seal is what keeps it dry.

> **TIP**
> If you have metal or tile, ask specifically whether the installer regularly works with that roof type. The method is different enough that experience with your exact roof matters more than with plain shingle.

15 Red Flags During and After the Install

Most crews do careful, watertight work. These are the warning signs that the roof side is being rushed, during the job and in the weeks after.

- Mounts screwed down with no flashing — just a blob of sealant over the hole.
- Relying on caulk or 'goop' alone instead of proper metal flashing to shed water.
- Bolts that clearly missed the rafters and went only into the thin roof decking.
- Loose, cracked, or lifted shingles left around the mounts after the crew leaves.
- Any damp smell, stain, or drip in the attic appearing in the months after the install.

> **WATCH OUT**
> Sealant alone is the classic shortcut. Good sealant helps, but it dries, cracks, and fails over the years — proper flashing is what keeps a roof dry for decades. If you only see caulk where the mounts meet the roof, that is worth questioning.

16 Common Myths About Solar and Roof Damage

Fear of roof damage keeps some folks from solar entirely, often on the strength of a myth. Here is the honest version.

- Myth: drilling into the roof means it will leak. Reality: a properly flashed penetration is as watertight as any vent pipe, and homes have those for decades.

- Myth: panels trap water and rot the roof. Reality: a gap under the panels lets air move and actually shades and protects the roof beneath.
- Myth: solar always voids your roof warranty. Reality: it depends on the roofer; often the panel area is simply excluded, not the whole warranty.
- Myth: you can never reroof once panels are up. Reality: panels can be removed and reset by a pro — plan the roof first and you rarely need to.

> **GOOD TO KNOW**
>
> The shaded, ventilated roof under a well-mounted array often ages a little more slowly than the exposed roof around it. Done right, panels protect the roof under them rather than harm it.

17 Words You'll Hear

A plain-English glossary for the mounting-and-leaks conversation.

Term	What it means in plain English
Penetration	A hole made through the roof for a bolt — normal, if sealed right
Flashing	The metal piece that channels water around a penetration to keep it dry
Lag bolt	The big screw that anchors a mount into the rafter
Rafter	The wooden beam under the roof the bolts must hit for a solid hold
Decking	The thin wood sheet under the shingles — too weak to hold bolts alone
Underlayment	The waterproof layer under the shingles that backs up the flashing

Workmanship warranty	The installer's promise to fix install faults, including leaks

TIP

If a conversation talks about 'flashing' and 'hitting the rafters,' that is a good sign — those are exactly the two things that keep a solar roof dry and solid for the long haul.

18 When to Call Bill

You do not have to sort any of this out alone, and there is real value in having someone with no panel to sell read a quote beside you.

I do not sell or install solar — I am the independent local tech who helps folks in Portage County, with 30-plus years of putting technology into plain English. The roof-leak worry is really about installer quality, and I am glad to help you ask the right questions, judge whether an installer's answers about flashing and warranties hold up, and decide whether your roof should be replaced before any panels go on.

- You are worried panels will leak or damage your roof.
- You want help judging an installer's flashing and workmanship answers.
- You are unsure whether to replace your roof before solar.
- You want a neutral read before trusting someone to drill into your roof.

CHEAT SHEET

Everyday Cheat Sheet

Keep this handy when weighing solar and worrying about your roof.

I want to...	Do this...
Understand the risk	Panels attach through the roof; proper flashing keeps those points dry
Know the real factor	Leaks come from careless installs, not from panels themselves
Trust the method	Flashing is century-old roofing craft, like a chimney collar
Avoid the big trap	Replace an old roof BEFORE solar, never after
Get protection in writing	Choose a strong, long installer workmanship warranty on penetrations
Catch trouble early	Watch ceilings/attic after heavy rain; never climb the roof yourself
Get help	Call Bill: (330) 200-8042

BEFORE YOU GO

A Note From Bill

A quick note from Bill. I write these guides to make home tech a little less frustrating, and I do my best to keep every step accurate and up to date. Still, every home, device, and setup is a bit different, so I can't promise a guide will match yours exactly or fix your particular problem. These guides are for general information only — they're not professional, legal, or financial advice, and they don't replace your device's own manual or the manufacturer's instructions. Please go slow, use your own good judgment, and use everything here at your own risk. If a step involves electrical wiring, a gas appliance, a water heater, plumbing, or climbing a ladder — or if anything just doesn't feel safe — please stop and call a licensed professional (or give me a call at 330-200-8042). Bill's Home Tech and Bill Davis can't be responsible for any damage, data loss, or injury that results.

HOW I CAN HELP

Your Visit — and My Promise

You don't have to remember all of it — just that a friendly, patient person is one call away, whenever you'd rather have a hand.

KEY SPECS

In your home — $99 flat for the first visit, no contracts and no surprises, with a 30-day come-back-free follow-up. In-home visits cover Portage County, Ohio and nearby communities.
Outside the area? Remotely — $49 for a screen-share session (free for Support Plan members, $39/mo), refundable if I can't fix it — and credited toward a visit if you'd rather have me in person. Book either at billshometech.com/book.

GOOD TO KNOW

My promise — If you're not 100% satisfied with your visit, I'll come back at no charge, or refund the full $99. No questions, no awkwardness. That's how I'd want to be treated.

Whenever you're ready, I'll come to your home anywhere in Portage County, Ohio and nearby communities, at your pace. Too far for a house call? I also help remotely. Book at billshometech.com/book or call (330) 200-8042. — Bill

Call or text (330) 200-8042 · bill@billshometech.com

This free guide is for general information only — not professional advice, and no substitute for your device's own manual. Any prices or outside products mentioned can change; please confirm current details before you buy. Please use your own good judgment and follow it at your own risk — for anything involving electricity, gas, water, or heights, stop and call a licensed professional. Bill's Home Tech and Bill Davis can't be responsible for any damage, data loss, or injury that results. © 2026 Bill's Home Tech, LLC.